





SCREW SPECIFICATIONS

Hex Washer Head Series

BI-METALL SCREWS



1 .Stainless Steel 304-A2 , Drill Point Size NO.1.....	1
2 . Stainless Steel 304-A2 , Drill Point Size NO.2.....	2
3 . Stainless Steel 304-A2 , Drill Point Size NO.3.....	6
4 . Stainless Steel 304-A2 , Drill Point Size NO.5.....	8
5 . Window Screw Stainless Steel 304-A2.....	9

1. Stainless Steel 304-A2 , Drill Point Size NO.1



Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	4.8X20mm	10	1.25+1.25mm
	4.8X22mm	12	1.25+1.25mm
	4.8X35mm	23	1.25+1.25mm
	5.5X22mm	12	1.25+1.25mm
	5.5x35mm	23	1.25+1.25mm
	6.3x25mm	13	1.25+1.25mm
	6.5x50mm	38	0.75+WOOD
	6.3/7.0x80mm	67	0.75+WOOD
	6.3/7.0x102mm	89	0.75+WOOD
	6.3/7.0x122mm	109	0.75+WOOD
	6.3/7.0x142mm	129	0.75+WOOD
	6.3/7.0x162mm	149	0.75+WOOD
	6.3/7.0x177mm	164	0.75+WOOD

3-1 : HEX:8mm Screw Driver Speed : Maximum 2500R.P.M

2. Stainless Steel 304-A2 , Drill Point Size NO.2


Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
 	4.2X16mm	8	2X0.6 - 2.5mm
	4.2X19mm	9	2X0.6 - 3.0mm

2-1 : HEX: 7mm Screw Driver Speed : Maximum 2500R.P.M

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
 	4.8X16mm	8	1.2 - 2.5mm
	4.8X19mm	8	1.2 - 4.5mm
	4.8X25mm	13	1.2 - 4.5mm


2-2 : HEX: 8mm Screw Driver Speed : Maximum 2500R.P.M

K. TICHU INDUSTRIES CO., LTD
 帝潮實業有限公司

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	5.5X25mm	11	1.2-3.5mm
	5.5X28mm	14	1.2-3.5mm
	5.5X32mm	18	1.2-3.5mm
	5.5X38mm	24	1.2-3.5mm
	5.5X50mm	36	1.2-3.5mm
	5.5X60mm	46	1.2-3.5mm
	5.5X75mm	61	1.2-3.5mm
	5.5X80mm	66	1.2-3.5mm

2-3 : HEX: 8mm


Screw Driver Speed : Maximum 2500R.P.M

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	5.5/6.3X70mm	56	1.2-3.5mm
	5.5/6.3X85mm	71	1.2-3.5mm
	5.5/6.3X110mm	96	1.2-3.5mm
	5.5/6.3X125mm	111	1.2-3.5mm
	5.5/6.3X145mm	131	1.2-3.5mm
	5.5/6.3X175mm	161	1.2-3.5mm
	5.5/6.3X195mm	181	1.2-3.5mm


2-4 : HEX: 8mm

Screw Driver Speed : Maximum 2500R.P.M

K. TICHO INDUSTRIES CO., LTD
 帝潮實業有限公司


Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	6.3X25mm	10	1.5-3.5mm
	6.3X32mm	17	1.5-3.5mm
	6.3X38mm	23	1.5-3.5mm
	6.3X50mm	35	1.5-3.5mm
	6.3X75mm	60	1.5-3.5mm
	6.3X80mm	65	1.5-3.5mm
	6.3X100mm	85	1.5-3.5mm
	6.3X115mm	100	1.5-3.5mm
	6.3X125mm	110	1.5-3.5mm
	6.3X150mm	135	1.5-3.5mm

2-5 : HEX: 8mm Screw Driver Speed : Maximum 1800R.P.M

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	6.3/7.0X100mm	85	1.5-3.5mm
	6.3/7.0X115mm	100	1.5-3.5mm
	6.3/7.0X125mm	110	1.5-3.5mm
	6.3/7.0X150mm	135	1.5-3.5mm
	6.3/7.0X175mm	160	1.5-3.5mm
	6.3/7.0X200mm	185	1.5-3.5mm
	6.3/7.0X225mm	210	1.5-3.5mm

2-6 : HEX:10mm Screw Driver Speed : Maximum 1800R.P.M


3. Stainless Steel 304-A2 , Drill Point Size NO.3

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	5.5X25mm	10	2 - 6mm
	5.5X28mm	13	2 - 6mm
	5.5X32mm	17	2 - 6mm
	5.5X38mm	23	2 - 6mm
	5.5X50mm	35	2 - 6mm
	5.5X75mm	60	2 - 6mm

1-1 : HEX :8mm Screw Driver Speed : Maximum 2500R.P.M

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	5.5/6.3X70mm	55	2 - 6mm
	5.5/6.3X85mm	70	2 - 6mm
	5.5/6.3X110mm	95	2 - 6mm
	5.5/6.3X125mm	110	2 - 6mm
	5.5/6.3X145mm	130	2 - 6mm
	5.5/6.3X175mm	160	2 - 6mm
	5.5/6.3X195mm	180	2 - 6mm

1-2 : HEX :8mm Screw Driver Speed : Maximum 2500R.P.M

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	6.3X25mm	10	2 - 6mm
	6.3X32mm	17	2 - 6mm
	6.3X38mm	23	2 - 6mm
	6.3X50mm	35	2 - 6mm
	6.3X75mm	60	2 - 6mm
	6.3X80mm	65	2 - 6mm
	6.3X100mm	85	2 - 6mm
	6.3X115mm	100	2 - 6mm
	6.3X125mm	110	2 - 6mm
	6.3X150mm	135	2 - 6mm

1-3 : HEX: 10mm Screw Driver Speed : Maximum 1800R.P.M


Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	6.3/7.0X100mm	85	2 - 6mm
	6.3/7.0X115mm	100	2 - 6mm
	6.3/7.0X125mm	110	2 - 6mm
	6.3/7.0X150mm	135	2 - 6mm
	6.3/7.0X175mm	160	2 - 6mm
	6.3/7.0X200mm	185	2 - 6mm
	6.3/7.0X225mm	210	2 - 6mm

1-4 : HEX:10mm Screw Driver Speed : Maximum 1800R.P.M

4. Stainless Steel 304-A2 , Drill Point Size NO.5

Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	5.5X40mm	15	4-12.5mm
	5.5X50mm	25	4-12.5mm
	5.5X60mm	35	4-12.5mm
	5.5X75mm	50	4-12.5mm
	5.5X80mm	55	4-12.5mm
	5.5X100mm	75	4-12.5mm

4-1 : HEX:8mm Screw Driver Speed : Maximum 1500R.P.M


Hex Washer Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	5.5/6.3X70mm	45	4-12.5mm
	5.5/6.3X85mm	60	4-12.5mm
	5.5/6.3X100mm	75	4-12.5mm
	5.5/6.3X110mm	85	4-12.5mm
	5.5/6.3X125mm	100	4-12.5mm
	5.5/6.3X145mm	120	4-12.5mm
	5.5/6.3X175mm	150	4-12.5mm
	5.5/6.3X195mm	170	4-12.5mm

4-2 : HEX:8mm Screw Driver Speed : Maximum 1500R.P.M

5. Window Screw Stainless Steel 304-A2

Pan Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	4.5X16mm	8	1.2 – 2.5mm
	4.5X19mm	9	1.2 – 2.5mm
	4.5X25mm	15	1.2 – 2.5mm
	4.5X28mm	18	1.2 – 2.5mm

5-1 : PAN HEAD , Screw Driver Speed : Maximum 2500R.P.M

Countersunk Head	Size	Stainless Steel Length (mm)	Application Plate Thickness (mm)
	4.5X16mm	8	1.2 – 2.5mm
	4.5X19mm	10	1.2 – 2.5mm
	4.5X25mm	15	1.2 – 2.5mm
	4.5X28mm	18	1.2 – 2.5mm
	4.5X32mm	22	1.2 – 2.5mm
	4.5X38mm	28	1.2 – 2.5mm
	4.5X45mm	35	1.2 – 2.5mm

5-2 : COUNTERSUNK HEAD , Screw Driver Speed : Maximum 2500R.P.M